

1. Unique identification code of the product-type: **Elements of Chimney Endings OSŁONA KOMINOWA**
2. Intended usage of the construction product: Elements of Chimney Endings -the cover of chimney and ventilation outlets, weather protection.
3. Manufacturer:



**"Komin-Flex" sp. z o.o.**  
**43-200 Pszczyna**  
**ul. Górnośląska 1**

4. Authorized representative: not applicable
5. System of assessment and verification of constancy of performance of the construction product: **4**
- 6a. Harmonized norm: PN EN 1856-1(2) 2009

**Technický a Zkušební Ústav Stavební Praha, s.p. (Technical and Test Institute for Construction Prague, State Facility)**  
**Notified Body EU No 1020, Number of certificate: 1939/2011**


7. Declared operational properties:

No.	Basic characteristics	Declared Technical Parameters	Harmonized technical specification PN-EN 1856-1: 2009
1.	Compressive strength	<b>1,5 [kN]</b>	<b>PN-EN 1856-1: 2009 item 6</b>
2.	Fire resistance Distance from flammable materials	<b>G (resistant) 500 [mm]</b>	<b>PN-EN 1856-1: 2009 item 6</b>
3.	Gas tightness Method of operation of the chimney	<b>N1 40 [Pa] negative pressure</b>	<b>PN-EN 1856-1: 2009 item 6</b>
4.	Flow resistance : average roughness	<b>Average roughness 0.1 R [mm]</b>	<b>PN-EN 1856-1: 2009 item 6</b>
5.	Heat penetration resistance	<b>0 [m²K/W]</b>	<b>PN-EN 1856-1: 2009 item 6</b>
6.	Resistance to soot fire Nominal Temp. work sys. chimney	<b>G (resistant) T250</b>	<b>PN-EN 1856-1: 2009 item 6</b>
7.	Bending strength	<b>NPD</b>	<b>NPD</b>
8.	Tightness after heat tests	<b>N1 40 [Pa]</b>	<b>PN-EN 1856-1: 2009 item 6</b>
9.	Resistance to water and steam diffusion Resistance to the effects of condensate	<b>resistant W</b>	<b>PN-EN 1856-1: 2009 item 6</b>
10.	Material type Resistance to corrosion Material thickness	<b>1.4301, 1.4307* Vm 0,5[mm]</b>	<b>PN-EN 1856-1: 2009 item 6</b>
11.	Resistance to freezing and thawing	<b>resistant</b>	<b>PN-EN 1856-1: 2009 item 6</b>

\*NOTE: Manufacturer's declaration of the type of the applied steel

Operational properties of the product defined above are consistent with operational properties declared in item.  
This declaration of commercial properties is released under the sole responsibility of the manufacturer specified in item 3.

Signed on behalf of the manufacturer by:

  
**Paweł Jerszynski – President**

**Pszczyna, 18 May 2023**